

ROMEX® D7000

Rock Dust Stabilizer

Product ID: 1 liter #108 | 5 Gallon #561

D7000 binds aggregate with fines to create a stable, durable surface. For installation, prepare and compact the base, place 1 inch (25mm) of the selected aggregate, and compact it again with a plate compactor. Then apply D7000 evenly using a watering can or pump sprayer to lock the surface together and help prevent washout, rutting, and aggregate migration.

Ideal for pathways and commercial surface applications.

- **Aggregates with fines**
- **Environmentally friendly**
- **Easy topical application**
- **Safe for people and pets**
- **Reduces erosion on sloped areas**
- **Dust reduction and stability on gravel surfaces**
- **Minimises weed growth**



Compatible with any aggregate with fines!

SCAN FOR MORE INFO

No Erosion

Weed Resistant

Topical Application

Easy to Use

ADA Compliant

1-844-529-2330 | www.romexhardscapes.com | info@romexhardscapes.com

ROMEX® D7000

Rock Dust Stabilizer

APPLICATION

Site Requirements: Excavation of 4-6” is recommended. Non-woven geotextile separation is optional. Ensure the subgrade is well compacted 0-3/4” road gravel and free of settlement to 98% proctor density using a mist of water to keep it damp during this process. Ensure a test of the aggregate with D7000 has been completed. Edging in the form of plastic, metal , wood or concrete is recommended.

Preparation: Ensure the base of 4-6” (100-150mm) is fully compacted in lifts using a mist of water keeping the gravel damp but not wet, and has sufficient slope or crown for drainage. Use angular gravel mixtures from 0-1/4” (0-5mm) with fines such as decomposed granite and stonedust screenings 1" | 25mm thick as the top finishing layer. Tape off adjacent areas that are not to be treated. Compact the surface until smooth before applying D7000.

Application: Outline 85sf (8sq m) sections with flags or marking paint. Pour the contents into a watering can using a funnel with an inclined spray attachment and distribute evenly over the surface.

Professional Tip: For heavily used surfaces, reapply ROMEX D7000 after hardening using a sprayer or watering can for added strength. Resealing requirements: approximately 350 square feet per 5 gal | 20 litre container, repeated every 3 years depending on surface use.

Subsequent Treatment: Protect the treated area from rain for the full 48-hour curing period, ensuring air circulation under the rain protection.

Important Information: Insufficient fines/dust content in gravel mixtures will result in variable binding results. Wear proper personal protective equipment (PPE) during work. Regularly remove moss, leaves, and weeds from the surface. Some or occasional stone detachment may occur depending on the installation, aggregate choice and traffic, which is natural and not a defect. D7000 needs surface and air temperatures of 10°C | 50°F or above for the full curing period of up to 48 hours. As aggregate qualities can vary, a mockup or sample area is always recommended prior to install. Re-open to pedestrian traffic after 48 hours. D7000 is for pedestrian use only.

Weather Warning: Only install at surface and air temperatures between 10°C – 30°C | 50°F – 86°F that will stay at or above 10°C | 50°F for the full curing period of up to 48 hours. D7000 will not cure below 10°C | 50°F, and an application that fails to cure will not cure later when it warms up. Check the 48-hour forecast. No rain for 48 hours after application; use an elevated cover if rain is expected. Do not install on frozen ground.

Loading	Depth	Coverage / x1 Unit
Pedestrian only	1" | 25mm approx.	85 sqft

Technical Data	
Water permeability	After application the covering basically remains just as permeable to water as before the application
Shelf life	12 months
Storage	Frost-free, protect container against direct sun light



PREPARE

Prepare approx 1" | 25mm of loose aggregate with fines



COMPACT

Compact for smoothness



APPLY

Pour container of D7000 from a watering can and distribute evenly over 85 SF



COMPLETE

Cure for 48 hours at 10°C | 50°F or above, protected from rain



TOP COAT (OPTIONAL)

Top coat for high-traffic pedestrian areas

CALL BEFORE YOU INSTALL

@romexhardscapes

1-844-529-2330 | www.romexhardscapes.com | info@romexhardscapes.com